



Stahlbiegeleiste HG						Außenmaße und Radien in mm Abmessungen nach DIN EN 1992-1-1
Pos.	Anz.	Ø [mm]	Länge [m]	Total- Länge [m]	Gewicht [kg]	
1	324	12	1,80	583,20	517,88	
2	404	16	2,15	866,60	1372,39	
3	152	8	2,54	386,08	152,50	
4	8	12	7,75	62,00	55,06	
5	12	12	7,75	33,00	29,30	
6	398	12	10,00	3980,00	3534,24	
7	42	12	7,11	296,62	265,17	
8	341	8	2,13	726,33	286,90	
9	1785	12	12,00	21420,00	19020,96	
10	102	12	6,98	711,96	632,22	
11	58	12	8,48	491,84	436,75	
12	76	12	5,75	437,38	388,39	
13	128	12	9,78	1251,84	1111,63	
14	2007	12	7,00	20349,00	18669,91	
15	12	12	2,96	35,58	31,60	
16	33	8	3,73	123,09	48,62	
17	6	8	2,33	13,95	5,51	
18	50	8	1,64	82,00	32,38	
19	16	12	9,40	150,40	133,56	
20	18	8	0,82	14,76	5,83	
21	50	8	1,62	81,00	32,00	
22	32	12	3,30	105,60	83,77	
23	384	12	11,46	4396,72	3906,06	
24	65	12	7,94	516,42	458,59	
25	48	12	10,67	511,92	454,58	
26	20	12	4,62	92,40	82,05	
27	20	12	9,61	192,10	170,58	
28	20	12	5,86	117,20	104,07	
29	130	12	11,65	1514,50	1344,88	
30	406	12	9,00	3654,00	3244,75	
31	78	12	4,55	354,90	315,15	
32	121	12	3,00	363,00	322,34	
33	259	12	1,77	457,14	405,94	
34	114	12	7,19	819,66	727,86	
35	276	12	5,80	1600,80	1421,51	
36	1	12	4338,42	4338,42	1277,31	
37	2088	8	1,62	3382,56	1336,11	
38	48	12	4,00	192,00	170,50	
39	12	12	9,04	108,42	96,28	
40	18	12	3,85	69,21	61,45	
41	140	12	3,60	504,00	447,55	
42	200	12	6,00	1740,00	1545,12	
43	26	12	3,70	96,20	85,43	
44	20	12	5,50	110,00	97,58	
45	57	8	0,90	51,30	20,26	
46	36	8	1,15	41,40	16,35	
47	3	8	1,71	5,12	2,02	
48	3	8	0,72	2,16	0,85	
49	6	8	1,16	6,96	2,75	
50	3	8	2,06	6,20	2,45	
51	3	8	1,22	3,66	1,45	

[illegible]